



GT OTJ435 43 Inch LED-Framed Curved Touchmonitor (J-type)

With J Type format, 4K UHD, vibrant colors, GT LED-Framed Curved Touch Monitors, allow for more impressive visual contents and captivating play. Sleek appearance, engaging visuals and accurate PCAP multi-touch experience let excited players immerse into the gaming atmosphere and enjoyment. It's an ideal touch solution widely used in the gaming, casino and sports betting.

Features & Benefits

- Unique Industrial-grade Design
- Curved 1500R Comfortable Viewing Experience
- Accurate PCAP Multi-touch Technology
- Front LED Lights, RGB/Addressable Modes
- 4K Resolution
- VESA Mounting, Portrait or Landscape
- Edge-to-edge Design, Easy to Clean
- DVI, HDMI, DP Interface



Applications

- Gaming
- Retail
- Amusement Industry

SPECIFICATIONS

Name	43 Inch LED-Framed Curved Touchmonitor (J-type)
Model	OTJ435-RC5000-UD5420-1.0
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD with LED Backlight
Aspect Ratio	16:9
Active Area (W x H)	941.18 × 529.42 mm
Native Resolution	3840 × 2160 @ 60 Hz
Response Time (Typ.)	8 ms
Display Colors	1.07 B
Luminance (Typ.)	500 nits
Contrast Ratio (Typ.)	1100:1
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 89°/89°
	Vertical (up/down) CR≥10 89°/89°
Touch Screen Parameters	
Touch Technology	Projected Capacitive (PCAP)
Surface Treatment	Tempered or Chemically Strengthened
Thickness (Total)	4.5 mm
Light Transmission	≥83%
Response Time (Typ.)	10 ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Black
Radius	1500 R
Mounting Options	VESA: 600 × 300 mm
Outline Dimensions (W×H×D)	1010.1 mm × 603.2 mm× 144.8 mm
Power Supply	Monitor: Input Voltage Range: +24 VDC ± 5% RGB LED Lights: +12 VDC ± 5% Optional LED controller(External): +12 VDC ± 5%
On Screen Display (OSD)	Control (remote): Power, Auto, Up, Down, Menu
Power Consumption (Max.)	100 W (Monitor without RGB LED Lights) 30 W (RGB LED Lights)
Operating Altitude	≤3000 m
System support	Win 7 or later, Linux 4.4 or later

Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	HDMI, DVI, DP, USB (Type B)
Accessories	Optional
Carton Box Dimensions (1 unit in one carton)	1180 mm (L) × 275 mm (W) × 770 mm (H)
Weight	Net: 24 kg Gross: 30 kg
MTBF	50,000 hours demonstrated
LED Lights Color	Multicolor
LED Lights Location	2 LED lights bar (Front), 3 LED lights bar (Back)
LED Controller (external)	Optional
Agency Approvals	CE, FCC
Warranty	1 year

Ordering Information

Model	Part Number	Description
OTJ435-RC5000-UD5420-1.0	110303500R	43" "J type", 4K, 16:9, 500 nits, PCAP, USB, HDMI/DVI/DP, 2 LED lights bar (Front), 3 LED lights bar (Back)

Contact sales for other options

Optional Accessories

Model	Part Number	Description
Adaptor	130104171R	G99-KEP150M-N001 Input:100-240V(VAC)-Output :24(VDC)-6.25A-150W-4PIN
Power Cable		1500 mm
USB Cable	130300224R	USB Cable, 1500 mm, male to male
DVI Cable	130300720R	DVI Cable, 1500 mm ,male to male
HDMI Cable	130300881R	1500 mm
DP Cable	130300932R	1500 mm
LED Controller Kit	110200887R	LED Controller Kit 50 W

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>