




GT OTJ505 50 Inch Curved Touchmonitor (J-type)

With J Type format, 4K UHD, GT Curved Touch Monitors, allow for more impressive visual contents and captivating play. Sleek appearance, engaging visuals and accurate PCAP multi-touch experience let excited players immerse into the gaming atmosphere and enjoyment. It's an ideal touch solution widely used in the gaming, casino and sports betting.

Features & Benefits

- Unique Industrial-grade Design
- Curved 1500R Comfortable Viewing Experience
- Accurate PCAP Multi-touch Technology
- 4K Resolution
- External VESA Mounting, Portrait or Landscape
- Edge-to-edge Design, Easy to Clean
- Customization Possible







SPECIFICATIONS

Name50 Inch Curved Touchmonitor (J-type)			
Model OTJ505-RC5000-UD5400-2.0			
LCD Panel Parameters			
Display Technology Active Matrix TFT-LCD With LED Backlight			
Aspect Ratio 16:9			
Active Area (W x H) 1095.84×616.41mm	1095.84×616.41mm		
Native Resolution 3840×2160@60Hz			
Response Time (Typ.) 8ms			
Display Colors 1.07B			
Luminance (Typ.) 500nits			
Contrast Ratio (Typ.) 4000:1			
Viewing Angle (Typ.)Horizontal (left/right) CR≥10 89°/89°Vertical (up/down) CR≥10 89°/89°			
Touch Screen Parameters			
Touch Technology Projected Capacitive (PCAP)			
Surface Treatment Tempered or Chemically Strengthened			
Thickness (Total) 4.5 ± 0.5 mm			
Light Transmission $\geq 83\%$			
Response Time (Typ.) 10ms			
Touch Screen Interface USB			
Touch Point 10			
Overall Parameters			
Case/Bezel Color Black			
Radius 1500R			
Mounting Options VESA: 600×400 mm			
Outline Dimensions (W×H×D) 1144.0 mm × 670.0mm × 167.5mm	1144.0mm × 670.0mm × 167.5mm		
Power Supply Input Voltage Range: +24VDC ± 5%			
On Screen Display (OSD) Control (back): Power, Auto, Up, Down, Menu			
Power Consumption (Max.) 130W			
Operating Altitude <3000m			
Operating Altitude $\leq 3000 \text{m}$			



Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C		
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%		
I/O	HDMI, DVI, DP, USB (Type B)		
Accessories	Optional		
Carton Box Dimensions (1 unit in one carton)	1269mm (L) × 306mm (W) × 824mm (H)		
Weight	Net: 29kg Gross: 36kg		
MTBF	50,000 hours demonstrated		
Agency Approvals	CE, FCC		
Warranty	1 year		

Ordering Information		
Model	Part Number	Description
OTJ505-RC5000-UD5400-2.0	110303343R	50" "J type", 16:9, 500nits, PCAP, USB, HDMI/DVI/DP

Contact sales for other options

Optional Accessories				
Model	Part Number	Description		
Adaptor	130104171R	G99-KEP150M-N001 Input:100-240V(VAC)- Output :24(VDC)-6.25A-150W-4PIN		
Power Cable		1500mm		
USB Cable	130300224R	1500mm, male to male		
DVI Cable	130300720R	1500mm, male to male		
HDMI Cable	130300881R	1500mm, male to male		
DP Cable	130300932R	1500mm, male to male		

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change , without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120 Fax: 0086-28-85124115 E-mail: info@generaltouch.com http://www.generaltouch.com