



50 Inch "J type" Closed Frame Touch Monitor

OTJ505 is a Curved Touch Monitor, As GT's 5th generation PCAP touch monitor solution is ideal not only for gaming applications but also for those small and large interactive digital signage displays where fast, accurate and sensitive touch solution is required. These monitors are available if you want to attract customers to the latest, largest and most exciting gaming experience possible.

Features & Benefits

- Curved R1500, black closed-frame designs
- 10-touch PCAP for windows 7 or later, Linux 4.4 or later
- 4K resolution









Applications

Gaming

■ SLOT

Casino



SPECIFICATIONS

Name	50 Inch "J type" Closed Frame Touch Monitor		
Model	OTJ505		
LCD Panel Parameters			
Display Technology	Active Matrix TFT-LCD With LED Backlight		
Aspect Ratio	16:9		
Active Area (W x H)	1095.84×616.41mm		
Native Resolution	3840×2160@60Hz		
Response Time (Typ.)	9.5ms		
Display Colors	1.07B		
Luminance (Typ.)	500nits; with PCAP 415nits		
Contrast Ratio (Typ.)	4000:1		
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 89°/89°		
Viewing Angle (1 yp.)	Vertical (up/down) CR≥10 89°/89°		
Touch Screen Parameters			
Touch Technology	Projected Capacitive (PCAP)		
Surface Treatment	Tempered or Chemically Strengthened Optional: Anti-Glare		
Thickness(Total)	4.5±0.5mm		
Light Transmission	≥83%		
Response Time (Typ.)	10ms		
Touch Screen Interface	USB		
Touch Point	10		
Overall Parameters			
Case/Bezel Color	Black		
Radius	Panel Frame R1500 (Cover Glass R1493.2)		
Mounting Options	VESA: 600 × 400 mm		
Outline Dimensions ($W \times H \times D$)	1144.0mm × 670.0mm× 167.5mm		
Power Supply	Input Voltage Range: +24VDC ± 5%		
On Screen Display (OSD)	Control (back): Power, Auto, Up, Down, Menu		
Power Consumption (Max.)	150W		
Operating Altitude	≤3000m		
System Support	Windows 7 or later, Linux 4.4 or later		



	0		
Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C		
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%		
I/O	HDMI, DVI, DP, USB (Type B)		
Accessories	Optional		
Carton Box Dimensions	$1269 \text{mm} (L) \times 306 \text{mm} (W) \times 824 \text{mm} (H)$		
(1 unit in one carton)	1207mm (2) / 300mm (w) / 024mm (11)		
Weight	Net: 29kg Gross: 36kg		
MTBF	50,000 hours demonstrated		
Agency Approvals	CE, FCC		
Warranty	1 year		

Ordering Information				
Model	Part Number Description			
OTJ505-RC5000-UD5400-1.0	110303079R 50" "J type", 16:9, 500nits, PCAP, USB, HDMI/DVI/DP			

Contact sales for other options

Optional Accessories		
Model	Part Number	Description
Adaptor	130104171R	G99-KEP150M-N001 Input:100-240V(VAC)-Output :24(VDC)-6.25A-150W-4PIN
Power Cable		1500mm
USB Cable	130300224R	USB Cable, 1500mm, male to male
DVI Cable	130300720R	DVI Cable, 1500mm ,male to male
HDMI Cable	130300881R	1500mm
DP Cable	130300932R	1500mm

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change , without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

http://www.generaltouch.com