



Premium Product


- >Multi-touch
- >Precision Engineering
- >Eye-Catching

7 Inch Open Frame Touch Monitor

OTL073 is a touchmonitor using industrial grade LED, with low power consumption, ultra-thin body design, high resolution display and excellent multi-touch interactive experience. Compared to the average consumer TV or monitor, the OTL073 industrial-grade high performance and professional design is better suited for applications in industries such as retail, gaming, kiosk, self-service, finance, transit, conference, education and healthcare.

Features & Benefits

- P-Cap technology
- Sleek appearance
- Continues to work even with scratched touchscreen
- Easy integration and low maintenance
- Excellent performance, accuracy and reliability with drift-free operation



Applications

- Retail
- Office
- Medical
- Finance
- Self-service
- Transport
- Gaming
- Kiosk

SPECIFICATIONS

Name	7 Inch Open Frame Touch Monitor
Model	OTL073
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD With LED Backlight
Aspect Ratio	16:10
Active Area (W x H)	149.76(H) x 93.60(V) mm
Native Resolution	1280 × 800@60Hz
Response Time (Typ.)	35ms
Display Colors	16.7million
Luminance (Typ.)	400nits; with P-Cap 332nits
Contrast Ratio (Typ.)	800:1
Viewing Angle (Typ.)	Horizontal (left/right) CR \geq 10 88°/88°
	Vertical (up/down) CR \geq 10 88°/88°
Touch Screen Parameters	
Touch Technology	Projected Capacitive (P-Cap)
Surface Treatment	Tempered Strengthened
	Optional: Anti-Glare
Active Area(W x H)	151.76x95.60 \pm 0.3mm
Thickness(Total)	2.8 \pm 0.2mm
Light Transmission	\geq 83%
Response Time	8~10ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Black
Mounting Options	Side Mounting
Outline Dimensions (W×H×D)	190.60x154.60x48.0mm
Power Supply	External Adapter: 100-240V AC, 50-60 Hz
	Input Voltage Range: +12VDC \pm 5%, DC Jet \varnothing 2.5mm
On Screen Display (OSD)	Control (back): Power, Auto, Up, Down, Menu
Power Consumption	MAX: 14W
Speaker	NA
Webcam	NA

Operating Altitude	≅ 3000m
Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	VGA, HDMI, USB (Type B, For touch)
Accessories	Cables: VGA × 1, USB × 1, 1.5m Length
Carton Box Dimensions	380mm (L) × 280mm (W) × 144mm (H)
Weight	Net: 1.46kg Gross: 2.6kg
MTBF	50,000 hours demonstrated
Agency Approvals	CE , FCC
Warranty	3 years

Ordering Information

Model	Part Number	Description
OTL073-RC3000-UH4A00-1.0	110303517R	7", 16:10, 400nits, P-Cap, USB, VGA & HDMI, Black

Contact sales for other options

Optional Accessories

Model	Part Number	Description
Adaptor	130102978R	12V/4.17A, DC Cable: 1500mm, DC Jet Ø2.5mm
HDMI Cord	130300881R	1500mm
	130300338R	UK
Power Cord	130300339R	EU 1500mm
	130300340R	US

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>