

## GT OTL153 15" Open Frame Touchmonitor



OTL153 is a touchmonitor using industrial grade LED, with low power consumption, ultra-thin body design, high resolution display and excellent multi-touch interactive experience. Compared to the average consumer TV or monitor, OTL153 industrial-grade high performance and professional design is better suited for applications in industries such as retail, gaming, kiosk, self-service, finance, transit, conference, education and healthcare.

### Features & Benefits

- Accurate PCAP Multitouch Technology
- Sleek Appearance
- Anti-scratch Touchscreen
- External VESA Mounting
- Easy Integration and Low Maintenance
- VGA, DVI Interface
- Commercial-grade Continuous (24/7) Use
- Optional Anti-glare



### Applications

- Retail
- Corporation
- Medical
- Banking
- Self-service
- Gaming
- Kiosk
- Transportation

## SPECIFICATIONS

Name	15" Open Frame Touchmonitor
Model	OTL153
<b>LCD Panel Parameters</b>	
Display Technology	Active Matrix TFT-LCD with LED Backlight
Aspect Ratio	4:3
Active Area (W x H)	304.13 × 228.10mm
Native Resolution	1024 × 768@60Hz
Response Time (Typ.)	23ms
Display Colors	16.2million
Luminance (Typ.)	350nits; with PCAP 298nits
Contrast Ratio (Typ.)	2500:1
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 88°/88° Vertical (up/down) CR≥10 88°/88°
<b>Touch Screen Parameters</b>	
Touch Technology	Projected Capacitive (PCAP)
Surface Treatment	Tempered Strengthened Optional: Anti-glare
Active Area(W x H)	308.1 × 232.1 ± 0.3mm
Thickness(Total)	2.4 ± 0.3mm
Light Transmission	≥85%
Response Time	8~10ms
Touch Screen Interface	USB
Touch Point	10
<b>Overall Parameters</b>	
Case/Bezel Color	Gray
Mounting Options	VESA: 100 × 100 mm; 75 × 75 mm; Side Mounting
Outline Dimensions (W×H×D)	350.22mm × 274.22mm × 44.0mm
Power Supply	External Adapter: 100-240V AC, 50-60 Hz Input Voltage Range: +12VDC ± 5%
On Screen Display (OSD)	Control (back): Power, Auto, Up, Down, Menu
Power Consumption (Typ.)	15W
Speaker	NA
Webcam	NA

Operating Altitude	≅ 3000m
Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	VGA, DVI, USB (Type B)
Accessories	Cables: VGA × 1, USB × 1, 1.5m Length
Carton Box Dimensions (4 units in 1 carton)	450mm (L) × 310mm (W) × 410mm (H)
Weight	Net: 3.46kg Gross: 16.62kg
MTBF	50,000 hours demonstrated
Agency Approvals	CCC, CE, FCC
Warranty	3 years

#### Ordering Information

Model	Part Number	Description
OTL153-RPC03-UCDA	110301258R	15", 4:3, 350nits, PCAP, USB, VGA & DVI, Gray

*Contact sales for other options*

#### Optional Accessories

Model	Part Number	Description
Adaptor	130102978R	12V/4.17A, DC Cable: 1500mm, DC Jet Ø2.5mm
Power Cord		UK/EU/US 1500mm
DVI Cord	130300720R	1500mm

Go to [www.generaltouch.com](http://www.generaltouch.com) for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

**Tel:** 0086-28-85124120

**Fax:** 0086-28-85124115

**E-mail:** [info@generaltouch.com](mailto:info@generaltouch.com)

<http://www.generaltouch.com>