



Premium Product

>Multi-touch

>Precision Engineering

>Eye-Catching

New Release!

17 Inch Open Frame Touch Monitor

OTL17L is a touchmonitor using industrial grade LED, with low power consumption, ultra-thin body design, high resolution display and excellent multi-touch interactive experience. Compared to the average consumer TV or monitor, the OTL17L industrial-grade high performance and professional design is better suited for applications in industries such as retail, gaming, kiosk, self-service, finance, transit, conference, education and healthcare.

Features & Benefits

- P-Cap technology
- Sleek appearance
- Continues to work even with scratched touchscreen
- Easy integration and low maintenance
- Excellent performance, accuracy and reliability with drift-free operation

Applications

- Retail
- Office
- Medical
- Finance
- Self-service
- Transport
- Gaming
- Kiosk

SPECIFICATIONS

Name	17 Inch Open Frame Touch Monitor
Model	OTL17L
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD With LED Backlight
Aspect Ratio	5:4
Active Area (W x H)	337.92 × 270.34mm
Native Resolution	1280 × 1024@60Hz
Response Time (Typ.)	12ms
Display Colors	16.7million
Luminance (Typ.)	500nits; with P-Cap 415nits
Contrast Ratio (Typ.)	1000:1
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 80°/80°
	Vertical (up/down) CR≥10 75°/75°
Touch Screen Parameters	
Touch Technology	Projected Capacitive (P-Cap)
Surface Treatment	Tempered Strengthened
	Optional: Anti-Glare
Active Area(W x H)	341.92 × 274.32 ± 0.3mm
Thickness(Total)	5.3 ± 0.3mm
Light Transmission	≥83%
Response Time	8ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Gray
Mounting Options	VESA: 100 × 100 mm; 75 × 75 mm; Side Mounting
Outline Dimensions (W × H × D)	380.00mm(W) × 317.50mm(H) × 59.60mm(D)
Power Supply	External Adapter: 100-240V AC, 50-60 Hz Input Voltage Range: +12VDC ± 5%
On Screen Display (OSD)	Control (back): Power, Auto, Up, Down, Menu
Power Consumption	MAX: 22W
Speaker	NA
Webcam	NA

Operating Altitude	≅ 3000m
Temperature Range	Operating: 0°C to 50°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	VGA, HDMI, USB (Type B)
Accessories	Cables: VGA × 1, USB × 1, 1.5m Length
Carton Box Dimensions (3 sets in 1 carton)	500mm (L) × 370mm (W) × 460mm (H)
Weight (3 sets in 1 carton)	Gross: 4.2kg Net: 15.22kg
MTBF	50,000 hours demonstrated
Agency Approvals	CCC, CE , FCC
Warranty	1 year

Ordering Information

Model	Part Number	Description
OTL17L-RC6000-UH5100-1.0		17", 5:4, 500nits, P-Cap, USB, VGA & HDMI, Gray

Contact sales for other options

Optional Accessories

Model	Part Number	Description
Adaptor	130102978R	12V/4.17A, DC Cable: 1500mm, DC Jet Ø2.5mm
Power Cord	UK/EU/US	1500mm
HDMI Cord	130300881R	1500mm

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>