

GT OTL195 19" Closed Frame Touchmonitor (iSurface)



GT Closed frame touch monitor with iSurface touch technology, available in 15, 17, 19, 27 inch, not only inherits the advantages of traditional SAW products, such as high reliability, high durability, high clarity, and scratch resistance but also can provide dustproof, waterproof, vandal-proof, anti-glare optional. The LED backlight module provides a slim look, longer life, and lower power consumption for the touch monitor. It's the best choice for various public applications such as self-service, kiosks, interactive digital signage, etc.

Features & Benefits

- Zero-bezel SAW Technology (iSurface)
- Superior Image Quality
- Anti-scratch Touchscreen
- Sleek Appearance
- Easy Integration and Low Maintenance
- VGA, DVI Interface
- Commercial-grade Continuous (24/7) Use
- VESA Mounting/ Wall Mounting



Applications

- Retail
- Corporation
- Medical
- Banking
- Self-service
- Gaming
- Kiosk
- Transportation

SPECIFICATIONS

Name	19" Closed Frame Touchmonitor (iSurface)
Model	OTL195-RZ03-SUCD
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD with LED Backlight
Aspect Ratio	5:4
Active Area (W x H)	376.32mm×301.06mm
Native Resolution	1280×1024 @ 60Hz
Response Time (Typ.)	5ms
Display Colors	16.7 million
Luminance (Typ.)	250nits; with SAW 225nits
Contrast Ratio (Typ.)	1000:1
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 85°/85°
	Vertical (up/down) CR≥10 80°/80°
Touch Screen Parameters	
Touch Technology	SAW
Surface Treatment	Optional: Anti-glare
Active Area	378.32mm×303.06mm
Thickness(Total)	3.00±0.2mm
Light Transmission	≥90%
Response Time	10.4ms
Touch Screen Interface	USB / RS232
Touch Point	1
Overall Parameters	
Case/Bezel Color	Black
Mounting Options	VESA: 75×75mm, 100×100mm
Outline Dimensions (W×H×D)	430.00mm×353.00mm×37.60mm
Power Supply	External Adapter: 100-240V AC, 50-60 Hz Input Voltage Range: +12VDC ± 5%
On Screen Display (OSD)	Control (back): Power, Auto, Up, Down, Menu
Power Consumption	MAX: 25W
Operating Altitude	≅ 3000m

Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	VGA, DVI, USB (Type B) , RS232
Accessories	Cables: VGA×1, USB×1, Power Cord, 1.5m Length Adaptor: 12V/3.33A, DC Cable: 1500mm, DC Jet Ø2.5mm
Carton Box Dimensions (1 unit in one carton)	530mm×460mm×185mm
Weight	Gross: 10kg Net: 7kg
MTBF	50,000 hours demonstrated
Agency Approvals	CCC, CE , FCC, UL
Warranty	3 years

Ordering Information

Model	Part Number	Description
OTL195-RZ03-SUCD	110301440R	19", 5:4, 250nits, Zero bezel SAW, USB & RS232, VGA/DVI

Optional Accessories

Model	Part Number	Description
DVI Cable	130300720R	DVI Cable length 1500mm 18+1pin male to male
RS232 Cable	130300291R	RS232 Cable CCS175A-APT12

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change , without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>