


GT OTL245 23.8 Inch LED-Framed Touchmonitor



GT 5-series LED-Framed Monitor is available in 23.8", 27", 32" display sizes. Fast and drift-free 10-point PCAP touch performance, vivid colors, and eye-catching front addressable LED illumination to keep exciting players immersed with captivating play. It is designed specifically for the rigors of gaming environments such as the casino, gaming, and amusement industry.

Features & Benefits

- LED-Framed, front 2 LED lights bar, back 3 LED lights bar
- High-quality PCB-mounted LEDs, no dark corners
- Independent LED lights bar interface for multi screen combination
- Accurate PCAP Multi-touch Technology
- True-flat, aluminum middle frame edging
- Black closed-frame designs



LED Lights
Model: C2521HF-3P



Applications

- Gaming
- SLOT
- Casino

SPECIFICATIONS

| | |
|--------------------------------|--|
| Name | 23.8 Inch LED-Framed Touchmonitor |
| Model | OTL245-RC5000-UP2F20-1.0 |
| LCD Panel Parameters | |
| Display Technology | Active Matrix TFT-LCD With LED Backlight |
| Aspect Ratio | 16:9 |
| Active Area (W x H) | 527.04 × 296.46mm |
| Native Resolution | 1920 × 1080@60Hz |
| Response Time (Typ.) | 14ms |
| Display Colors | 16.7M |
| Luminance (Typ.) | 250nits |
| Contrast Ratio (Typ.) | 1000:1 |
| Viewing Angle (Typ.) | Horizontal (left/right) CR \geq 10 89°/89° Vertical (up/down) CR \geq 10 89°/89° |
| Touch Screen Parameters | |
| Touch Technology | Projected Capacitive (PCAP) |
| Surface Treatment | Tempered Optional: Anti-Glare |
| Thickness (Total) | 4.3 ± 0.3mm |
| Light Transmission | ≥83% |
| Response Time (Typ.) | 8ms |
| Touch Screen Interface | USB |
| Touch Point | 10 |
| Overall Parameters | |
| Case/Bezel Color | Dark grey |
| Mounting Options | VESA: 100 × 100 mm, 75 × 75mm, 150 × 450mm |
| Outline Dimensions (W × H × D) | 583.20mm × 341.25mm × 50.10mm |
| Power Supply | Monitor: Input Voltage Range: +12VDC ± 5% RGB LED Lights: +5VDC ± 5% Optional LED controller (external): +12VDC ± 5% |
| On Screen Display (OSD) | Control (back): Power, Auto, Up, Down, Menu |
| Power Consumption (Max.) | 36W (Monitor without RGB LED Lights) 30W (RGB LED Lights) |
| Operating Altitude | ≤3000m |
| System support | Win7 or later, Linux 4.4 or later |

| | |
|--|---|
| Temperature Range | Operating: 0°C to 40°C, storage: -20°C to 60°C |
| Humidity (Non Condensing) | Operating: 20% to 80%, storage: 10% to 90% |
| I/O | VGA, DVI, DP, USB (Type B) |
| Accessories | Optional |
| Carton Box Dimensions (2 units in one carton) | 690mm (L) × 260mm (W) × 460mm (H) |
| Weight | Net: 8kg Gross: 20kg |
| MTBF | 50,000 hours demonstrated |
| LED Lights Color | Multicolor |
| LED Lights Location | Front: 2 LED lights bar, Back: 3 LED lights bar |
| LED Controller (external) | Optional |
| Agency Approvals | CE , FCC |
| Warranty | 3 years |

Ordering Information

| Model | Part Number | Description |
|--------------------------|-------------|---|
| OTL245-RC5000-UP2F20-1.0 | 110302715R | 23.8", 16:9, 250nits, PCAP, USB, VGA/DVI/DP, LED lights Location front & back |

Optional Accessories

| Model | Part Number | Description |
|--------------------|-------------|---|
| VGA Cable | 130300697R | VGA Cable, 1500mm OD5.8 male to male 15PIN, black |
| USB Cable | 130300224R | USB Cable, 1500mm, male to male |
| DVI Cable | 130300720R | DVI Cable, 1500mm, 18+1pin, male to male |
| DP Cable | 130300932R | DP Cable, 1500mm, 20pin to 20pin, male to male, black |
| Adaptor | 130102978R | KPL-050F-VI 12V/4.17A DC 1500mm Ø 2.5 50W UL level VI |
| Power Cable | | 1500mm |
| LED Controller Kit | 110200853R | LED Controller Kit, 30W |

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>