GT OTL24Y
23.6" Circular Closed Frame Touchmonitor

23.6" circular display, with FHD resolution, fast and drift-free 10-point PCAP touch performance, keeps exciting players immersed with captivating play. It is designed specifically for the rigors of gaming environments such as the casino, gaming, and amusement.

Features & Benefits

- Circular display
- FHD resolution 1280×1280
- Accurate PCAP Multi-touch Technology
- True Flat and Black Closed-frame Design
- External VESA Mounting
- Commercial-grade Continuous (24/7) Use





Applications

- Gaming
- SLOT
- Retail

© 2022 General Touch Co., Ltd. All rights reserved

SPECIFICATIONS

Name	23.6 Inch Circular Closed Frame Touch Monitor
Model	OTL24Y
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD with LED Backlight
Aspect Ratio	1:1
Active Area (W x H)	599.42×599.42mm
Native Resolution	1280×1280@60Hz (The host needs to input 1920×1280 resolution to the display, and other resolutions are not supported.)
Response Time (Typ.)	14ms
Display Colors	16.7M
Luminance (Typ.)	700nits, with PCAP 581nits
Contrast Ratio (Typ.)	1000:1
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 89°/89° Vertical (up/down) CR≥10 89°/89°
Touch Screen Parameters	
Touch Technology	Projected Capacitive (PCAP)
Surface Treatment	Tempered or Chemically Strengthened Optional: Anti-Glare
Thickness(Total)	3.5mm
Light Transmission	≥83%
Response Time (Typ.)	10ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Rear shell: Black Shield: Gray
Mounting Options	VESA: 200×150 mm
Outline Dimensions（W×H×D）	674.6mm × 674.6mm× 55.6mm (φ674.6mm)
Power Supply	Input Voltage Range: +24VDC ± 5%
On Screen Display (OSD)	Control (back): Power, Auto, Up, Down, Menu
Power Consumption (Max.)	100W
Operating Altitude	≤3000m
System support (PCAP)	Win7 or later, Linux 4.4 or later

© 2022 General Touch Co., Ltd. All rights reserved

Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	VGA, HDMI, USB (Type B)
Accessories	Optional
Carton Box Dimensions (1 unit in one carton)	785 mm (L) × 785 mm (W) × 185 mm (H)
Weight	Net: 11.9 kg Gross: 17.6 kg
MTBF	50,000 hours demonstrated
Agency Approvals	CE, FCC
Warranty	3 years

Ordering Information		
Model	Part Number	Description
OTL24Y-RC4000-UHBT00-1.0	110303403R	23.6", circular, 1:1, 700nits, PCAP, USB, VGA/HDMI

Optional Accessories		
Model	Part Number	Description
VGA Cable	130300697R	VGA Cable, 1500mm, male to male
USB Cable	130300224R	USB Cable, 1500mm, male to male
HDMI Cable	130300881R	HDMI Cable, 1500mm, male to male
Adaptor	130105053R	Input:100-240V(VAC)-Output :24(VDC)-5A-120W-4PIN
Power Cable		1500mm

Go to www.generaltouch.com for more products and information, or contact us.
General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change , without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120
Fax: 0086-28-85124115
E-mail: info@generaltouch.com
http://www.generaltouch.com

© 2022 General Touch Co., Ltd. All rights reserved