



## Premium Product

- >Multi-touch
- >Precision Engineering
- >Eye-Catching

### 32 Inch Closed Frame Touch Monitor

OTL325 is a LED Touchmonitor, with low power consumption, high brightness, FHD, ultra-thin body design, high resolution display and excellent multi-touch interactive experience. Compared to the average consumer TV or Computer, the OTL325 industrial-grade high performance and professional design is better suited for applications in industries such as retail, gaming, kiosk, self-service, finance, transport, conference, education and healthcare.

#### Features & Benefits

- P-Cap technology
- FHD
- Sleek appearance
- Continues to work even with scratched touchscreen
- Easy integration and low maintenance
- Excellent performance, accuracy and reliability with drift-free operation



#### Applications

- Retail
- Office
- Medical
- Finance
- Self-service
- Transport
- Gaming
- Kiosk

## SPECIFICATIONS

Name	32 Inch Closed Frame Touch Monitor
Model	OTL325
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD With LED Backlight
Aspect Ratio	16:9
Active Area (W x H)	698.40 × 392.85mm
Native Resolution	1920 × 1080@60Hz
Response Time (Typ.)	6.5ms
Display Colors	16.7M
Luminance (Typ.)	500nits; with P-Cap 425nits
Contrast Ratio (Typ.)	4000:1
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 89° /89° Vertical (up/down) CR≥10 89° /89°
Touch Screen Parameters	
Touch Technology	Projected Capacitive (P-Cap)
Surface Treatment	Strengthened Optional: Anti-Glare
Active Area(W x H)	698.40x393 ± 0.5mm
Thickness(Total)	4.3 ± 0.3mm
Light Transmission	≥85%
Response Time	10ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Silver middle frame with black back cover
Mounting Options	VESA: 200 × 200 mm;
Outline Dimensions (W × H × D)	750.0mm × 444.5mm × 63.7mm
Power Supply	Input Voltage Range: 24V DC
On Screen Display (OSD)	Control (Back): Power, Auto, Up, Down, Menu
Power Consumption	MAX: 73W
Speaker	NA
Webcam	NA

Operating Altitude	≅ 3000m
Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	VGA, HDMI, USB (Type B, For touch)
Accessories	Cables: VGA × 1, 1.5m Length, USB × 1, 1.5m Length
Carton Box Dimensions	910mm (L) × 220mm (W) × 630mm (H)
Weight	Net: 13.6kg Gross: TBD
MTBF	50,000 hrs
Agency Approvals	CE FCC
Warranty	3 years

#### Ordering Information

Model	Part Number	Description
OTL325-RC5000-UH5200-2.0	110303642R	32", 16:9, 1080P, 500nits, P-Cap, USB, VGA& HDMI

Contact sales for other options

#### Optional Accessories

Model	Part Number	Description
Power Cord	130301888R	UK
	130301494R	EU
	130301493R	US
HDMI Cord	130300881R	1500mm
Adaptor	130105053R	24V/5A, DC Cable: 1200mm, DC Jet 4PIN

Go to [www.generaltouch.com](http://www.generaltouch.com) for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: [info@generaltouch.com](mailto:info@generaltouch.com)

<http://www.generaltouch.com>