



Premium Product

- >Multi-touch
- >Precision Engineering
- >Eye-Catching

32 Inch Closed Frame Touch Monitor

OTL325 is a LED industrial Touchmonitor, with low power consumption, high brightness, FHD, ultra-thin body design, high resolution display and excellent multi-touch interactive experience. Compared to the average consumer TV or Computer, the OTL325 industrial-grade high performance and professional design is better suited for applications in industries such as retail, gaming, kiosk, self-service, finance, transport, conference, education and healthcare.

Features & Benefits

- P-Cap technology
- FHD
- Sleek appearance
- Continues to work even with scratched touchscreen
- Easy integration and low maintenance
- Excellent performance, accuracy and reliability with drift-free operation



Applications

- Retail
- Office
- Medical
- Finance
- Self-service
- Transport
- Gaming
- Kiosk

SPECIFICATIONS

Name	32 Inch Closed Frame Touch Monitor
Model	OTL325
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD With LED Backlight
Aspect Ratio	16:9
Active Area (W x H)	698.40 × 392.85mm
Native Resolution	1920 × 1080@60Hz
Response Time (Typ.)	6.5ms
Display Colors	16.7M
Luminance (Typ.)	400nits; with P-Cap 340nits
Contrast Ratio (Typ.)	4000:1
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 89° /89° Vertical (up/down) CR≥10 89° /89°
Touch Screen Parameters	
Touch Technology	Projected Capacitive (P-Cap)
Surface Treatment	Strengthened and Anti-Glare
Active Area(W x H)	699.50x393.4 ± 0.5mm
Thickness(Total)	5.3 ± 0.3mm
Light Transmission	≥85%
Response Time	10ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Silver middle frame with black back cover
Mounting Options	VESA: 200 × 100 mm
Outline Dimensions (W×H×D)	752.7mm × 447.3mm × 49.0mm
Power Supply	Input Voltage Range: 100-240V AC, 50-60 Hz
On Screen Display (OSD)	Control (Back): Power, Auto, Up, Down, Menu
Power Consumption	MAX: 75W
Speaker	2*5W
Webcam	NA

Operating Altitude	≅ 3000m
Temperature Range	Operating: 0°C to 50°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	VGA, HDMI, USB (Type B, For touch)
Accessories	Cables: VGA × 1, 1.5m Length, USB × 1, 1.5m Length
Carton Box Dimensions	910mm (L) × 220mm (W) × 630mm (H)
Weight	Net: 13.6kg Gross: 20.5kg
MTBF	50,000 hrs
Agency Approvals	CE FCC
Warranty	3 years

Ordering Information

Model	Part Number	Description
OTL325-RC60A0-UH4F0S-1.0	110303444R	32", 16:9, 1080P, 400nits, P-Cap, USB, VGA& HDMI

Contact sales for other options

Optional Accessories

Model	Part Number	Description
Power Cord	130300338R	UK
	130300339R	EU
	130300340R	US
HDMI Cord	130300881R	1500mm

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>