

GT OTL327 32" LED-Framed Touchmonitor



GT LED-Framed Monitor is available in 21.5", 23.8", 27", 32", and 43" display sizes. Fast and drift-free 10-point PCAP touch performance, vivid colors, and eye-catching front and edge addressable LED illumination keep exciting players immersed with captivating play. It is designed specifically for the rigors of gaming environments such as the casino, gaming, and amusement industry.

Features & Benefits

- High-quality PCB-mounted LEDs, no dark corners
- LED lights bar for surrounding display
- RGB LED light bar available
- True-flat, black closed-frame designs
- 10-touch PCAP for windows 7 or later, Linux 4.4 or later



LED Lights



DVI



DP




VGA



Power

USB



Applications

- Gaming
- SLOT
- Casino

SPECIFICATIONS

Name	32 Inch LED Lights Bar Closed Frame Touch Monitor
Model	OTL327
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD with LED Backlight
Aspect Ratio	16:9
Active Area (W x H)	698.40×392.85mm
Native Resolution	1920×1080@60Hz
Response Time (Typ.)	8ms
Display Colors	16.7M
Luminance (Typ.)	400nits
Contrast Ratio (Typ.)	1200:1
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 89°/89°
	Vertical (up/down) CR≥10 89°/89°
Touch Screen Parameters	
Touch Technology	Projected Capacitive (PCAP)
Surface Treatment	Tempered or Chemically Strengthened Optional: Anti-Glare
Thickness(Total)	4.3mm±0.3mm
Light Transmission	≥83%
Response Time (Typ.)	10ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Black
Mounting Options	VESA: 200×200 mm
Outline Dimensions (W×H×D)	765.9mm × 466.5mm× 59.6mm
Power Supply	Monitor: Input Voltage Range: +24VDC ± 5% RGB LED Lights: +5VDC ± 5% Optional LED controller(External): +12VDC ± 5%
On Screen Display (OSD)	Control (back): Power, Auto, Up, Down, Menu
Power Consumption (Max.)	60W (Monitor without RGB LED Lights) 30W (RGB LED Lights)
Operating Altitude	≤3000m
System support	Win7 or later, Linux 4.4 or later

Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	VGA, DVI, DP, USB (Type B)
Accessories	Optional
Carton Box Dimensions (1 unit in one carton)	905mm (L) × 215mm (W) × 630mm (H)
Weight	Net: 15kg Gross: 20kg
MTBF	50,000 hours demonstrated
LED Lights Color	Multicolor
LED Lights Location	4 LED lights bar (Front, Back & Edge)
LED Controller(remote)	Optional
Agency Approvals	CE , FCC
Warranty	3 years

Ordering Information		
Model	Part Number	Description
OTL327-RC5000-UP4F50-1.0	110303359R	32", 16:9, 400nits, PCAP, USB, VGA/DVI/DP, LED lights Location front & edge
Optional Accessories		
Model	Part Number	Description
VGA Cable	130300697R	VGA Cable, 1500mm
USB Cable	130300224R	USB Cable, 1500mm,
DVI Cable	130300720R	DVI Cable, 1500mm,
DP Cable	130300932R	DP Cable, 1500mm,
LED Controller Kit	110200850R	LED Controller Kit, 30W
Adaptor	130104171R	G99-KEP150M-N001 Input:100-240V(VAC)- Output :24(VDC)-6.25A-150W-DC 4PIN
Power Cable		1500mm

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change , without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>