



## Premium Product

- >Multi-touch
- >Precision Engineering
- >Eye-Catching

### 43 Inch Closed Frame Touch Monitor

OTL435 is a LED Touchmonitor, with low power consumption, high brightness, UHD, ultra-thin body design, high resolution display and excellent multi-touch interactive experience. Compared to the average consumer TV or Computer, the OTL435 industrial-grade high performance and professional design is better suited for applications in industries such as retail, gaming, kiosk, self-service, finance, transport, conference, education and healthcare.

#### Features & Benefits

- P-Cap technology
- UHD
- Sleek appearance
- Continues to work even with scratched touchscreen
- Easy integration and low maintenance
- Excellent performance, accuracy and reliability with drift-free operation



#### Applications

- Retail
- Office
- Medical
- Finance
- Self-service
- Transport
- Gaming
- Kiosk

## SPECIFICATIONS

Name	43 Inch Closed Frame Touch Monitor
Model	OTL435-RC5000-UD5U00-2.0
<b>LCD Panel Parameters</b>	
Display Technology	Active Matrix TFT-LCD With LED Backlight
Aspect Ratio	16:9
Active Area (W x H)	941.18(H) x 529.42(V) mm
Native Resolution	3840×2160@60Hz
Response Time (Typ.)	8ms
Display Colors	1.07G
Luminance (Typ.)	500nits; with P-Cap 415nits
Contrast Ratio (Typ.)	1200:1
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 89° /89° Vertical (up/down) CR≥10 89° /89°
<b>Touch Screen Parameters</b>	
Touch Technology	Projected Capacitive (P-Cap)
Surface Treatment	Strengthened Optional: Anti-Glare
Active Area(W x H)	942.0x530.0±0.5mm
Thickness(Total)	4.3±0.3mm
Light Transmission	≥85%
Response Time	10ms
Touch Screen Interface	USB
Touch Point	10
<b>Overall Parameters</b>	
Case/Bezel Color	Silver middle frame with black back cover
Mounting Options	Wall Mount, See The Drawing
Outline Dimensions (W×H×D)	1031.0mm × 619.0mm× 80.2mm
Power Supply	Input Voltage Range: 100~240V AC
On Screen Display (OSD)	Control (Back): Power, Auto, Up, Down, Menu
Power Consumption	MAX: 95W
Speaker	NA
Webcam	NA

Operating Altitude	≅ 3000m
Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	DP, HDMI, HDMI, USB (Type B, For touch)
Accessories	Cable: USB × 1, 1.5m Length
Carton Box Dimensions	TBD
Weight	Net: 22.5kg Gross: TBD
MTBF	50,000 hrs
Agency Approvals	CE FCC
Warranty	3 years

### Ordering Information

Model	Part Number	Description
OTL435-RC5000-UD5U00-2.0	110303643R	43", 16:9, 4K, 500nits, P-Cap, USB, DP& HDMI&HDMI

Contact sales for other options

### Optional Accessories

Model	Part Number	Description
Power Cord	130301888R	UK
	130301494R	EU
	130301493R	US
HDMI Cord	130300881R	1500mm
DP Cord	130300932R	1500mm

Go to [www.generaltouch.com](http://www.generaltouch.com) for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: [info@generaltouch.com](mailto:info@generaltouch.com)

<http://www.generaltouch.com>