

## GT OTL436 43" Open Frame Touchmonitor



OTL436 is a touchmonitor using industrial grade LED, with low power consumption, ultra-thin body design, high resolution display and excellent multi-touch interactive experience. Compared to the average consumer TV or monitor, OTL436 industrial-grade high performance and professional design is better suited for applications in industries such as retail, gaming, kiosk, self-service, finance, transit, conference, education and healthcare.

### Features & Benefits

- Accurate PCAP Multitouch Technology
- Sleek Appearance
- Anti-scratch Touchscreen
- VESA Mounting
- Easy Integration and Low Maintenance
- VGA, HDMI, DVI, DP Interface
- Commercial-grade Continuous (24/7) Use
- Optional Anti-glare
- 3 Years Warranty



### Applications

- Retail
- Corporation
- Medical
- Banking
- Self-service
- Gaming
- Kiosk
- Transportation

## SPECIFICATIONS

Name	43" Open Frame Touchmonitor
Model	OTL436
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD with LED Backlight
Aspect Ratio	16:9
Active Area (W x H)	940.9×529.25mm
Native Resolution	1920×1080@60Hz
Response Time (Typ.)	8ms
Display Colors	16.7million
Luminance (Typ.)	400nits; with PCAP 340nits
Contrast Ratio (Typ.)	1200:1
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 89°/89°
	Vertical (up/down) CR≥10 89°/89°
Touch Screen Parameters	
Touch Technology	Projected Capacitive (PCAP)
Surface Treatment	Chemically Strengthened
	Optional: Anti-glare
Active Area(W x H)	941.18×529.42±0.5mm
Thickness(Total)	4.8±0.3mm
Light Transmission	≥83%
Response Time	10ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Gray
Mounting Options	VESA: 400×200 mm
Outline Dimensions (W×H×D)	1021.0mm × 608.7mm× 54.2mm
Power Supply	Input Voltage Range: 100-240V AC, 50-60 Hz
On Screen Display (OSD)	Control (Back): Power, Auto, Up, Down, Menu
Power Consumption	MAX: 80W
Speaker	NA
Webcam	NA

Operating Altitude	≅ 3000m
Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	VGA, HDMI, DVI, DP, USB (Type B)
Accessories	Cables: VGA × 1, USB × 1, 1.5m Length
Carton Box Dimensions	1190mm (L) × 240mm (W) × 780mm (H)
Weight	Net: 24.2kg Gross: 28.6kg
MTBF	50,000 hours demonstrated
Agency Approvals	RoHS
Warranty	3 years

#### Ordering Information

Model	Part Number	Description
OTL436-RPCZ05-UHPCDAGN4	110302689R	43", 16:9, 400nits, PCAP, USB, VGA, DVI & HDMI & DP, Gray

*Contact sales for other options*

#### Optional Accessories

Model	Part Number	Description
Power Cord	130300338R	UK
	130300339R	EU
	130300340R	US
HDMI Cord	130300881R	1500mm
DP Cord	130300932R	1500mm
DVI Cord	130300720R	1500mm

Go to [www.generaltouch.com](http://www.generaltouch.com) for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

**Tel:** 0086-28-85124120

**Fax:** 0086-28-85124115

**E-mail:** [info@generaltouch.com](mailto:info@generaltouch.com)

<http://www.generaltouch.com>