




15 Inch Open Frame Touch Monitor

RTL15L is a LED industrial Touchmonitor, with low power consumption, ultra-thin body design, high resolution display and excellent multi-touch interactive experience. Compared to the average consumer TV or Computer, the RTL15L industrial-grade high performance and professional design is better suited for applications in industries such as retail, gaming, kiosk, self-service, finance, transport, conference, education and healthcare.

Features & Benefits

- P-Cap technology
- Sleek appearance
- Continues to work even with scratched touchscreen
- Easy integration and low maintenance
- Excellent performance, accuracy and reliability with drift-free operation



Applications

- Retail
- Office
- Medical
- Finance
- Self-service
- Transport
- Gaming
- Kiosk

SPECIFICATIONS

Name	15 Inch Open Frame Touch Monitor
Model	RTL15L-LC5000-UD3A00-1.0
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD With LED Backlight
Aspect Ratio	4:3
Active Area (W x H)	304.1 × 228.1mm
Native Resolution	1024 × 768@60Hz
Response Time (Typ.)	30ms
Display Colors	16.7million
Luminance (Typ.)	350nits; with P-Cap 298nits
Contrast Ratio (Typ.)	1000:1
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 88°/88°
	Vertical (up/down) CR≥10 88°/88°
Touch Screen Parameters	
Touch Technology	Projected Capacitive (P-Cap)
Surface Treatment	Strengthened
	Optional: Anti-Glare
Active Area(W x H)	305.1 × 229.1 ± 0.3mm
Thickness(Total)	4.3 ± 0.3mm
Light Transmission	≥83%
Response Time	8~10ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Black
Mounting Options	VESA: 75 × 75mm, 100 × 100 mm; Rear Mounting; Side Mounting
Outline Dimensions (W × H × D)	See The Drawing
Power Supply	External Adapter: 100-240V AC, 50-60 Hz Input Voltage Range: +12VDC ± 5%, DC Jet Ø2.1mm
On Screen Display (OSD)	Control (External): Power, Auto, Up, Down, Menu
Power Consumption	MAX: 17W
Speaker	NA
Webcam	NA

Operating Altitude	≤3000m
Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	VGA, HDMI, DP, USB (Type B), Mini Din(External OSD)
Accessories	Cables: VGA × 1, USB × 1, 1.5m Length; OSD Remote
Carton Box Dimensions (2 units in one carton)	460mm (L) × 230mm (W) × 280mm (H)
Weight	Net: 3.52kg Gross: 9.4kg
MTBF	50,000 hours demonstrated
Agency Approvals	CE , FCC, UL
Warranty	3 years

Ordering Information

Model	Part Number	Description
RTL15L-LC5000-UD3A00-1.0	110303743L	15", 4:3, 350nits, P-Cap, USB, VGA & HDMI & DP, Black

Contact sales for other options

Optional Accessories

Model	Part Number	Description
Adaptor	130104158R	12V/5A, DC Cable: 1200mm, DC Jet ø2.1mm
	130301888R	UK
Power Cord	130301494R	EU 1500mm
	130301493R	US
HDMI Cord	130300881R	1500mm
DP Cord	130300932R	1500mm
Brackets	120400539R	See The Drawing

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

<http://www.generaltouch.com>