



## 19 Inch Open Frame Touch Monitor

RTL19L is a LED industrial Touchmonitor, with low power consumption, ultra-thin body design, high resolution display and excellent multi-touch interactive experience. Compared to the average consumer TV or Computer, the RTL19L industrial-grade high performance and professional design is better suited for applications in industries such as retail, gaming, kiosk, self-service, finance, transport, conference, education and healthcare.

### Features & Benefits

- P-Cap technology
- Sleek appearance
- Continues to work even with scratched touchscreen
- Easy integration and low maintenance
- Excellent performance, accuracy and reliability with drift-free operation



### Applications

- Retail
- Office
- Medical
- Finance
- Self-service
- Transport
- Gaming
- Kiosk

## SPECIFICATIONS

Name	19 Inch Open Frame Touch Monitor
Model	RTL19L-LC5000-UD2A00-1.0
<b>LCD Panel Parameters</b>	
Display Technology	Active Matrix TFT-LCD With LED Backlight
Aspect Ratio	5:4
Active Area (W x H)	374.78×299.83mm
Native Resolution	1280×1024@60Hz
Response Time (Typ.)	14ms
Display Colors	16.7million
Luminance (Typ.)	250nits; with P-Cap 210nits
Contrast Ratio (Typ.)	1000:1
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 89°/89°
	Vertical (up/down) CR≥10 89°/89°
<b>Touch Screen Parameters</b>	
Touch Technology	Projected Capacitive (P-Cap)
Surface Treatment	Strengthened
	Optional: Anti-Glare
Active Area(W x H)	376.4×300.8±0.3mm
Thickness(Total)	4.3±0.3mm
Light Transmission	≥83%
Response Time	8~10ms
Touch Screen Interface	USB
Touch Point	10
<b>Overall Parameters</b>	
Case/Bezel Color	Black
Mounting Options	VESA: 75×75mm, 100×100 mm; Rear Mounting; Side Mounting
Outline Dimensions (W×H×D)	See The Drawing
Power Supply	External Adapter: 100-240V AC, 50-60 Hz
	Input Voltage Range: +12VDC ± 5%, DC Jet Ø2.1mm
On Screen Display (OSD)	Control (External): Power, Auto, Up, Down, Menu
Power Consumption	MAX: 19W
Speaker	NA
Webcam	NA

Operating Altitude	≤3000m
Temperature Range	Operating: 0°C to 40°C, storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, storage: 10% to 90%
I/O	VGA, HDMI, DP, USB (Type B), Mini Din(External OSD)
Accessories	Cables: VGA × 1, USB × 1, 1.5m Length; OSD Remote
Carton Box Dimensions (2 units in one carton)	520mm (L) × 470mm (W) × 305mm (H)
Weight	Net: 4.82kg Gross: 12.2kg
MTBF	50,000 hours demonstrated
Agency Approvals	CE , FCC, UL
Warranty	3 years

#### Ordering Information

Model	Part Number	Description
RTL19L-LC5000-UD2A00-1.0	110303742L	19", 5:4, 250nits, P-Cap, USB, VGA & HDMI & DP, Black

Contact sales for other options

#### Optional Accessories

Model	Part Number	Description
Adaptor	130104158R	12V/5A, DC Cable: 1200mm, DC Jet ø2.1mm
	130301888R	UK
Power Cord	130301494R	EU 1500mm
	130301493R	US
HDMI Cord	130300881R	1500mm
DP Cord	130300932R	1500mm
Brackets	120400537R	See The Drawing

Go to [www.generaltouch.com](http://www.generaltouch.com) for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: [info@generaltouch.com](mailto:info@generaltouch.com)

<http://www.generaltouch.com>