

## 21.5 Inch

**Rear Mount Touchmonitor** 

## **RTL226**







Jam-packed with advanced technical features, the latest General Touch Rear Mount Touchmonitor has been engineered to meet demanding operating environments without compromising its aesthetic appeal. Crafted with industrial-grade materials and precision molding, one could tell it could worth its weight in gold just by looking and handling it.

At its heart, an EETI chip drives its PCAP touch functions, coupled with an edge-to-edge cover glass that attains IP65 rating (Front surface) and easily survives the IK07 ball-drop test. This tough nut performs even in diverse and hostile environments. No wonder, not all PCAP touchscreens are created the same. In certain sizes, the PCAP touchscreen is optically bonded to its industrial grade LCD panel that spells unparalleled motion imagery in its class that is lifelike and immersive for any users.

Other desirable physical features include svelte profile, both DP and HDMI interfaces, external OSD menu control and versatile mounting options with adjustable brackets provided. Backed by GT's 3-year warranty, this Rear Mount PCAP Touchmonitor is pleasing to the eye, potent to work with and pleasurable to operate. With sizes ranging from 10.1 to 43 inches, GT's Rear Mount Touchmonitors can be proudly deployed in sectors like Retail, Entertainment, Financial Equipment, Self-service Kiosk, Lottery, Transport, Industrial Automation and more.

- Flexible installation choices and adjustable mounting brackets render the equipment seamlessly compatible
- The hardware modular design embodies a sleek and integrated aesthetic, exuding a sense of fashionable sophistication
- Front-facing, it achieves the esteemed IP65 rating
- Externally tethered OSD facilitates remote image adjustments

Kiosk



Gaming



Vending Machine



Industrial Automation

- Three-year warranty
- A comprehensive range of 10.1 to 43 inches, facilitating all-in-one procurement
- In-house production of exceptional touchscreens, suitable for a myriad of industries
- Certain sizes offer the option of optical bonding technology, providing a more authentic display



## **SPECIFICATIONS**

Product Name	21.5 Inch Rear Mount Touchmonitor	
Model	RTL226	
LCD Panel Parameters		
Display Technology	Active Matrix TFT-LCD With LED Backlight	
Aspect Ratio	16:9	
Active Area (W x H)	476.64mm × 268.11mm	
Native Resolution	1920×1080@60Hz	
Response Time (Typ.)	18ms	
Display Colors	16.7million	
Luminance (Typ.)	250nits, with PCAP 225nits	
Contrast Ratio (Typ.)	3000:1	
Viewing Angle (Typ.)	Horizontal (left/right) CR≥10 89°/89°	
	Vertical (up/down) CR≥10_89°/89°	
Touch Screen Parameters		
Touch Technology	PCAP	
Surface Treatment	Strengthened Optional: Anti-Glare	
Active Area(W x H)	476.4mm × 268.1mm±0.3mm	
Thickness(Total)	3.3mm±0.3mm	
Light Transmission	≥85%	
Response Time	10ms	
Touch Screen Interface	USB	
Touch Point	10	
Overall Parameters		
Case/Bezel Color	Black	
Mounting Options	VESA: 100mm ×100 mm, Rear Mounting, Side Mounting	
Outline Dimensions (W×H×D)	516mm × 311mm × 37.9mm	
Power Supply	Input Voltage Range: +12V DC $\pm$ 5%, Coaxial power jack 2.1mm pin outer	
	diameter	
On Screen Display (OSD)	Control (External): Power, Auto, Up, Down, Menu	
Power Consumption	MAX: 20W	
Speaker	NA	
Webcam	NA	



Operating Altitude	≤3000m	
Temperature Range	Operating: 0 °C to 50 °C, Storage: -20 °C to 60 °C	
Humidity (Non Condensing)	Operating: 20% to 80%, Storage: 10% to 90%	
I/O	VGA, HDMI, DP, USB (Type B), Mini DIN (External OSD)	
Accessories	Cables: VGA×1, USB×1, 1.5m Length, Bracket×2, External OSD	
Carton Box Dimensions	630mm (L) $\times$ 250mm (W) $\times$ 430mm (H), 2 units in one carton	
Weight	Net: 5.56kg, Gross: 14.62kg	
MTBF	50,000 hours demonstrated	
Agency Approvals	CCC, CE, FCC, UL	
Warranty	3 years	

Ordering Information				
Model	Part Number	Description		
RTL226-LRPCZ04-UHPDA	10202010091L	21.5", 16:9, 250nits, PCAP, USB, VGA & HDMI & DP, Black		

Contact sales for other options

Ontional	Accession
Optional	Accessories

Model	Part Number	Description
Adapter	30207010011R	12V/5A, DC Cable: 1200mm, DC barrel plug 2.1mm pin inner diameter
	30301010018R	UK
Power Cable	30301010011R	EU 1500mm
	30301010010R	US
HDMI Cable	30302030001R	1500mm
DP Cable	30302010001R	1500mm

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120 Fax: 0086-28-85124115 E-mail: info@generaltouch.com http://www.generaltouch.com