



43 Inch Open Frame Touch Monitor

RTL436 is a LED industrial Touchmonitor, with low power consumption, ultra-thin body design, high resolution display and excellent multi-touch interactive experience. Compared to the average consumer TV or Computer, the RTL436 industrial-grade high performance and professional design is better suited for applications in industries such as retail, gaming, kiosk, self-service, finance, transport, conference, education and healthcare.

Features & Benefits

- P-Cap technology
- Sleek appearance
- Continues to work even with scratched touchscreen
- Easy integration and low maintenance
- Excellent performance, accuracy and reliability with drift-free operation





Applications

- Retail
- Office
- Medical
- Finance
- Self-service
- Transport

- Gaming
- Kiosk



SPECIFICATIONS

| Name | 43 Inch Open Frame Touch Monitor | | | |
|--|---|--|--|--|
| Model | RTL436 | | | |
| LCD Panel Parameters | | | | |
| Display Technology | Active Matrix TFT-LCD With LED Backlight | | | |
| Aspect Ratio | 16:9 | | | |
| Active Area (W x H) | 940.9 × 529.25mm | | | |
| Native Resolution | 1920×1080@60Hz | | | |
| Response Time (Typ.) | 8ms | | | |
| Display Colors | 16.7million | | | |
| Luminance (Typ.) | 450nits; with P-Cap 375nits | | | |
| Contrast Ratio (Typ.) | 1200:1 | | | |
| Viewing Angle (Typ.) | Horizontal (left/right) CR≥10 89°/89° Vertical (up/down) CR≥10 89°/89° | | | |
| Touch Screen Parameters | | | | |
| Touch Technology | Projected Capacitive (P-Cap) | | | |
| Surface Treatment | Strengthened Optional: Anti-Glare | | | |
| Active Area(W x H) | $942.4 \times 530.6 \pm 0.3$ mm | | | |
| Thickness(Total) | 3.4 ± 0.3 mm | | | |
| Light Transmission | ≥83% | | | |
| Response Time | 10ms | | | |
| Touch Screen Interface | USB | | | |
| Touch Point | 10 | | | |
| Overall Parameters | | | | |
| Case/Bezel Color | Gray | | | |
| Mounting Options | VESA: 400×400 mm; Rear Mounting; Side Mounting | | | |
| Outline Dimensions ($W \times H \times D$) | 746.6mm × 452.0mm× 57.70mm | | | |
| Power Supply | Input Voltage Range: 100-240V AC, 50-60 Hz | | | |
| On Screen Display (OSD) | Control (External): Power, Auto, Up, Down, Menu | | | |
| Power Consumption | MAX: 80W | | | |
| Speaker | NA | | | |
| Webcam | NA | | | |



| Operating Altitude | ≤3000m | | |
|---------------------------|---|--|--|
| Temperature Range | Operating: 0°C to 50°C, storage: -20°C to 60°C | | |
| Humidity (Non Condensing) | Operating: 20% to 80%, storage: 10% to 90% | | |
| I/O | VGA, HDMI, DP, USB (Type B), Mini Din(External OSD) | | |
| Accessories | Cables: VGA × 1, USB × 1, 1.5m Length; Bracket × 4; OSD Remote | | |
| Carton Box Dimensions | $1100\text{mm (L)} \times 220\text{mm (W)} \times 750\text{mm (H)}$ | | |
| Weight | Net: 24.2kg Gross: 28.6kg | | |
| MTBF | 50,000 hours demonstrated | | |
| Agency Approvals | CE, FCC | | |
| Warranty | 3 years | | |

| Ordering Information | | |
|--------------------------|-------------|---|
| Model | Part Number | Description |
| RTL436-RC4G00-UD4F00-1.0 | 110303418R | 43", 16:9, 450nits, P-Cap, USB, VGA & HDMI & DP, Gray |
| | | |

Contact sales for other options

| Optional Accessories | | | |
|----------------------|-------------|-------------|--------|
| Model | Part Number | Description | |
| | 130300338R | UK | |
| Power Cord | 130300339R | EU | 1500mm |
| | 130300340R | US | |
| HDMI Cord | 130300881R | 1500mm | |
| DP Cord | 130300932R | 1500mm | |

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change , without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120

Fax: 0086-28-85124115

E-mail: info@generaltouch.com

http://www.generaltouch.com